

MRT26



Tiltrotator

For 19 - 28 ton excavators.

Shallow construction.

Good torsional rigidity.

Cost-effective.

Features :



MCL Central lubrication system

MRT Central Lubrication is a factory-installed central lubrication system that can be connected to the lubrication system of the working machinery. A strong lubrication system genuinely designed for the Nordic winter conditions.



MHF High-flow hydraulics

MRT High Flow – now included as standard. Proportional control which provides over 100 l/min. of oil for attachments.



MCS steering controllers

MRT - MACS-proportional steering system with a touchscreen and L8-joystics. Check our selection of movement systems on page 8-9.

Factory-installed optional extras:



MG Gripper equipment

MRT Gripper, by equipping your working machinery with MRT Gripper, you can further increase the versatility of your equipment.



MPS Rotational sensor

MRT position system. Accurate sensor for 3D machine control systems.

Choose your preferred system: Novatron, Leica, Trimble, or Topcon.

MRT Hydraulic quick couplers

We supply most types of automatic quick coupling systems and tailor them suitable for your needs.

Ask for an offer.

Technical data:	
Width A	540
Width B	373
Width C	315
Width D	847
Width E	592
Weight kg	865
Pref. hydraulic oil flow l/min.	120
Max. hydraulic pressure -bar	210
Rotational moment kNm:	15
Upper attachment:	Direct,S70,S1,CW
Tool attachment:	S70,S1,CW

